

FIG. 1



FIG. 2



FIG. 3A



FIG. 3B



FIG. 3D



FIG. 3C



FIG. 3F



FIG. 3E



Figure 3G



Figure 3I



Figure 3H



Figure 3J



Figure 3K



Figure 3L



FIG. 5A



FIG. 5B



FIG. 4



FIG. 6A



FIG. 6B



FIG. 6C

FIG. 6D

FIG. 6E

Title: Methods, Systems, and Devices
for Evaluation of Thermal Treatment
Inventors: Palazoglu et al.
Attorney Docket No. 297/164/2



Figure 6F



FIG. 7A



FIG. 7B



FIG. 7C


A1
A2
S3
L1
S2
L2
S1
DP
A1
A2
S3
L1
S2
L2
S1
DP
A1
A2
S3
L4
S2
L3
S1
DP
IP
CP

Figure 7D


A1
S
Z
T1
Z
S
DP
A1
A2
S
Z
T1
S
Z
T1
Z
S
S
Z
T1
S
Z
T2
Z
S
A2
A1
S
Z
T3
Z
S
A3
IP
CP

Figure 7E

Title: Methods, Systems, and Devices
for Evaluation of Thermal Treatment
Inventors: Palazoglu et al.
Attorney Docket No. 297/164/2



Figure 7F



Figure 7G



FIG. 8



FIG. 9



FIG. 10



FIG. 11



FIG. 12



FIG. 13



FIG. 14A

FIG. 14B

FIG. 14C



FIG. 14D



FIG. 15


natural
Magnetic field strength
8
7
6
5
4
3
2
0
1000
2000
3000
4000
5000
6000
7000

FIG. 16



FIG. 17



FIG. 18



FIG. 19


glued and heated
non-identical magnet pair
Magnetic field strength
Temp (°C)
8
7
6
5
4
3
2
140
120
100
80
60
40
20
0

FIG. 20


Magnetic field strengt
Temperature (°C
Time (sec)
6
5
4
3
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200
250

FIG. 21


magnet pair+single magnet
Magnetic field streng
Temp (°C)
Time (sec)
136.6°C
6.5
6
5.5
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200
250

FIG. 22


Solder1 (MP = 138.3°C)
Magnetic field strength
Temp (°C)
Time (s)
138.1°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 23


Solder1 (MP = 138.3°C)
Magnetic field strength
Temp (°C)
Time (s)
137.0°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 24


Solder1 (MP = 138.3°C)
Magnetic field strength
Temp (°C)
Time (s)
137.6°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
120
170
220
270
320

FIG. 25


Solder1 (MP = 138.3°C)
Magnetic field strength
Temp (°C)
Time (s)
137.8°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 26


Solder1 (MP = 138.3°C)
Magnetic field strength
Temp (°C)
Time (s)
137.8°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 27


Solder2 (MP = 123.9°C)
Magnetic field strength
Temp (°C)
Time (s)
125.7°C
5
4.5
4
3.5
3
2.5
2
160
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 28


Solder2 (MP = 123.9°C)
Magnetic field strength
Temp (°C)
Time (s)
124.7°C
5
4.5
4
3.5
3
2.5
2
140
120
100
80
60
40
20
0
0
50
100
150
200

FIG. 29


Solder2 (MP = 123.9°C)
Magnetic field strength
5
4.5
4
3.5
3
2.5
2
124.4°C
140
120
100
80
60
40
20
0
Temp (°C)
0
50
100
150
200
Time (s)

FIG. 30


135 C - Trial2
Magnetic Response
Temperature
Magnetic Field Strength
2.56
2.55
2.54
2.53
2.52
2.51
2.5
2.49
2.48
180
160
140
120
100
80
60
40
20
0
Temperature (C)
Time

FIG. 31


138 C - Trial1
Magnetic Response
Temperature
Magnetic Field Strength
3
2.9
2.8
2.7
2.6
2.5
2.4
2.3
2.2
160
140
120
100
80
60
40
20
0
Temperature (C)
Time

FIG. 32


Dual temperature detection
Magnetic field strength
2.9
2.8
2.7
2.6
2.5
123.6°C
136.7°C
160
180
200
220
240
260
280
300
Time (s)

FIG. 33

Title: Methods, Systems, and Devices
for Evaluation of Thermal Treatment
Inventors: Palazoglu et al.
Attorney Docket No. 297/164/2



FIG. 34


CS
DISPLAY
D
MEMORY
MEM
SPATIAL
SIMULATION
ENGINE
SSE
COMP
USER
INTERFACE
UI

FIG. 35

FIG. 36


3600
START
3602
3604
STORE INFORMATION FOR SIMULATING A TARGET PARTICLE
3606
STORE INFORMATION FOR SIMULATING A CARRIER PARTICLE DESIGN
3608
DETERMINE THE CONSERVATIVE BEHAVIOR CHARACTERISTICS OF A TARGET PARTICLE
3610
DETERMINE MATERIALS AND DIMENSIONS FOR A CARRIER PARTICLE DESIGN ABOUT MATCHING THE CONSERVATIVE BEHAVIOR CHARACTERISTICS OF THE TARGET PARTICLE
3612
FABRICATE AN ACTUAL CARRIER PARTICLE ABOUT EQUIVALENT TO THE CARRIER PARTICLE DESIGN
STOP
3614

FIG. 37


3700
Cubic particle
1/2 in.
Polypropylene
F_0 = 3 min
3702
Potato
F_0 = 146 min

FIG. 38


3800
Cubic particle
3/8 in.
Polypropylene
F_0 = 3 min
3802
Potato
F_0 = 93 min

FIG. 39


3900
Cylindrical particle
1/2 in. x 1/2 in.
Polypropylene
F_0 = 3 min
3902
Potato
F_0 = 133 min

FIG. 40


4000
Cylindrical particle
3/8 in. x 3/8 in.
Polypropylene
F_0 = 3 min
4002
Potato
F_0 = 84 min


Cubic particle
1/2 in.
12.7 mm
4100
12.7 mm
A
B
Center of particle
D
C
4102
4104

FIG. 41

Potato
1/2 in.
F_0 (center) = 3 min.
Time = 131.4 s
(Holding only)
$\alpha = 1.63 \times 10^{-7}$ m²/s



FIG. 42

Potato
1/2 in.



FIG. 43

TPX
1/2 in.
Time = 131.4 s
(Holding only)
$\alpha = 1.04 \times 10^{-7}\ m^2/s$



FIG. 44

TPX
1/2 in.



FIG. 45

Nylon
1/2 in.
Time = 131.4 s
(Holding only)
$\alpha = 1.40 \times 10^{-7}$ m²/s



FIG. 46

Nylon
1/2 in.



FIG. 47

Teflon
1/2 in.
Time = 131.4 s
(Holding only)
$\alpha = 1.15 \times 10^{-7}$ m²/s



FIG. 48

Teflon
1/2 in.



FIG. 49

Polypropylene
1/2 in.
Time = 131.4 s
(Holding only)
$\alpha = 6.10 \times 10^{-8}$ m²/s

5000



FIG. 50

Polypropylene
1/2 in.

5100



FIG. 51


Cubic particle
3/8 in.
9.5 mm
5200
9.5 mm
A
B
Center of particle
D
C
5204
5202

FIG. 52

Potato
3/8 in.
F_0 (center) = 3 min.
Time = 82.1 s
(Holding only)
$\alpha = 1.63 \times 10^{-7}$ m²/s

5300



FIG. 53

Potato
3/8 in.

5400



23.2	23.6	24.4	25.8	27.7	30.3	33.8	38.7	45.7	56.2
14.8	15.1	15.8	16.9	18.6	20.8	24.0	28.5	35.2	45.7
10.2	10.5	11.1	12.0	13.4	15.4	18.2	22.3	28.5	38.7
7.5	7.7	8.2	9.0	10.2	12.0	14.5	18.2	24.0	33.8
5.8	6.0	6.4	7.1	8.1	9.7	12.0	15.4	20.8	30.3
4.6	4.8	5.2	5.8	6.7	8.1	10.2	13.4	18.6	27.7
3.9	4.1	4.4	4.9	5.8	7.1	9.0	12.0	16.9	25.8
3.4	3.6	3.9	4.4	5.2	6.4	8.2	11.1	15.8	24.4
3.1	3.3	3.6	4.1	4.8	6.0	7.7	10.5	15.1	23.6
	3.1	3.4	3.9	4.6	5.8	7.5	10.2	14.8	23.2

FIG. 54

TPX
3/8 in.
Time = 82.1 s
(Holding only)
$\alpha = 1.04 \times 10^{-7}$ m²/s



FIG. 55

TPX
3/8 in.



FIG. 56

Nylon
3/8 in.
Time = 82.1 s
(Holding only)
$\alpha = 1.40 \times 10^{-7}\ m^2/s$

5700



FIG. 57

Nylon
3/8 in.

5800



32.0	32.5	33.6	35.2	37.6	40.9	45.5	51.7	60.6	74.9
17.3	17.8	18.6	20.0	22.1	25.0	29.2	35.2	44.5	60.6
10.8	11.2	11.9	13.0	14.7	17.2	20.8	26.3	35.2	51.7
7.3	7.6	8.2	9.1	10.5	12.7	15.9	20.8	29.2	45.5
5.3	5.5	6.0	6.8	8.0	9.8	12.7	17.2	25.0	40.9
4.0	4.2	4.6	5.3	6.4	8.0	10.5	14.7	22.1	37.6
3.3	3.4	3.8	4.4	5.3	6.8	9.1	13.0	20.0	35.2
2.8	2.9	3.2	3.8	4.6	6.0	8.2	11.9	18.6	33.6
2.5	2.6	2.9	3.4	4.2	5.5	7.6	11.2	17.8	32.5
	2.5	2.8	3.3	4.0	5.3	7.3	10.8	17.3	32.0

FIG. 58

Teflon
3/8 in.
Time = 82.1 s
(Holding only)
$\alpha = 1.15 \times 10^{-7}\ m^2/s$



FIG. 59

Teflon
3/8 in.



21.1	21.6	22.6	24.3	26.6	30.0	34.6	41.3	51.2	67.4
8.6	8.9	9.6	10.7	12.4	14.8	18.6	24.3	33.7	51.2
4.1	4.3	4.8	5.5	6.7	8.5	11.3	16.0	24.3	41.3
2.2	2.4	2.7	3.2	4.0	5.3	7.5	11.3	18.6	34.6
1.3	1.4	1.6	2.0	2.6	3.6	5.3	8.5	14.8	30.0
0.8	0.9	1.1	1.3	1.8	2.6	4.0	6.7	12.4	26.6
0.6	0.6	0.7	1.0	1.3	2.0	3.2	5.5	10.7	24.3
0.4	0.5	0.6	0.7	1.1	1.6	2.7	4.8	9.6	22.6
0.4	0.4	0.5	0.6	0.9	1.4	2.4	4.3	8.9	21.6
	0.4	0.4	0.6	0.8	1.3	2.2	4.1	8.6	21.1

FIG. 60

Polypropylene
3/8 in.
Time = 82.1 s
(Holding only)
$\alpha = 6.10 \times 10^{-8}$ m²/s



FIG. 61

Polypropylene
3/8 in.



FIG. 62


Cylindrical particle
1/2 in. x 1/2 in.
12.7 mm
6300
12.7
mm
Center of particle
6302
6304

FIG. 63

Potato
1/2 in. x 1/2 in.
F_0 (center) = 3 min.
Time = 120.5 s
(Holding only)
$\alpha = 1.63 \times 10^{-7}$ m²/s



FIG. 64

Potato
1/2 in. x 1/2 in.



FIG. 65

TPX
1/2 in. x 1/2 in.
Time = 120.5 s
(Holding only)
$\alpha = 1.04 \times 10^{-7}$ m²/s



FIG. 66

TPX
1/2 in. x 1/2 in.



FIG. 67

Nylon
1/2 in. x 1/2 in.
Time = 120.5 s
(Holding only)
$\alpha = 1.40 \times 10^{-7}$ m²/s



FIG. 68

Nylon
1/2 in. x 1/2 in.



FIG. 69

Teflon
1/2 in. x 1/2 in.
Time = 120.5 s
(Holding only)
$\alpha = 1.15 \times 10^{-7}$ m²/s



FIG. 70

Teflon
1/2 in. x 1/2 in.



FIG. 71

Polypropylene
1/2 in. x 1/2 in.
Time = 120.5 s
(Holding only)
$\alpha = 6.10 \times 10^{-8}\ m^2/s$

7200



FIG. 72

Polypropylene
1/2 in. x 1/2 in.

7300



7302

7304

FIG. 73


Cylindrical particle
3/8 in. x 3/8 in.
9.5 mm
7400
9.5 mm
Center of particle
7404
7402

FIG. 74

Potato
3/8 in. x 3/8 in.
F_0 (center) = 3 min.
Time = 76.0 s
(Holding only)
$\alpha = 1.63 \times 10^{-7} m^2/s$

7500



FIG. 75

Potato
3/8 in. x 3/8

7600



7602

FIG. 76

TPX
3/8 in. x 3/8 in.
Time = 76.0 s
(Holding only)
$\alpha = 1.04 \times 10^{-7}$ m²/s



FIG. 77

TPX
3/8 in. x 3/8 in.



FIG. 78

Nylon
3/8 in. x 3/8 in.
Time = 76.0 s
(Holding only)
$\alpha = 1.40 \times 10^{-7}\ m^2/s$



FIG. 79

Nylon
3/8 in. x 3/8 in.



FIG. 80

Teflon
3/8 in. x 3/8 in.
Time = 76.0 s
(Holding only)
$\alpha = 1.15 \times 10^{-7}$ m²/s



FIG. 81

Teflon
3/8 in. x 3/8 in.



FIG. 82

Polypropylene
3/8 in. x 3/8 in.
Time = 76.0 s
(Holding only)
$\alpha = 6.10 \times 10^{-8}\ m^2/s$



FIG. 83

Polypropylene
3/8 in. x 3/8 in.



FIG. 84

FIG. 85


8500
START
8502
SIMULATE HEATING OF A TARGET FOOD PARTICLE UNTIL A TARGET LETHALITY IS ACCUMULATED
8504
SIMULATE A CARRIER PARTICLE UNDER SIMILAR CONDITIONS AND THE SAME TIME PERIOD
8506
DETERMINE CONSERVATIVE THICKNESS OF THE WALL BETWEEN THE INTERIOR CAVITY AND EXTERIOR OF THE CARRIER PARTICLE
8508
CALCULATE THE WEIGHT OF THE CARRIER PARTICLE
8510
STOP
8512



FIG. 86

8700



FIG. 87

8800



FIG. 88A

8802



FIG. 88B

8804

8900



FIG. 89A

8902

8904



FIG. 89B



FIG. 90A



FIG. 90B